

# OKINAWA ATF D IV

(Automatic Transmission Fluid)

## DESCRIPTION

OKINAWA ATF D IV is a Transmission fluid, designed for use in modern automatic gearboxes, where GM Dexron or Ford Mercon specifications are quoted.

## PRODUCT BENEFITS

- Exceptional low temperature fluidity.
- Excellent resistance to oxidation and high thermal stability
- Durability of friction characteristics and wear protection.
- Protection against rust and corrosion, and good seal compatibility
- Compatibility with new technologies, such as band clutches and new clutch plate materials
- OKINAWA ATF DIV does not contain sperm oil

## Recommendations / Specifications

OKINAWA ATF DIV meets DEXRON IV (GM 6297M/Opel/Vauxhall), Ford MERCON (M2C-185A)

It meets the requirement of Allison C4

## TYPICAL TECHNICAL PROPERTIES

Properties	Typical Value
Color, VISUAL	RED
Density at 15°C, g/ml, ASTM D4052	0.859
Kinematic Viscosity at 100°C, mm <sup>2</sup> /s, ASTM D445	6.8
Viscosity Index, ASTM D2270	185
Flash Point(COC), °C, ASTM D92	210
Pour Point, °C, ASTM D97	-48

**Note:** These characteristics are typical of current production. While future production will conform to OKINAWA's specification, variations in these characteristics may occur.

*PDS/ATF/011/0\*, 10.08.15, Page 1/1  
\* supersedes all previous versions*

---

*Health and Safety: Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contact office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing off used product, take care to protect the environment.*