

# OKINAWA SYNTHETIC ENGINE OIL C3 SAE 0W-30 SP

(Synthetic P.C.M.O.)

## DESCRIPTION

OKINAWA SYNTHETIC ENGINE OIL C3 SAE 0W-30 SP is an advanced full synthetic motor oil designed to help deliver outstanding engine protection and enhanced fuel economy benefits to keep your engine running like new and protect critical engine parts for up to 10,000 miles between oil changes. It meets or exceeds the requirements of the industry's toughest standards and outperforms our conventional and synthetic blend oils. OKINAWA SYNTHETIC ENGINE OIL C3 SAE 0W-30 SP, synthetic motor oil technology, comes as standard equipment in many different vehicles, including select high-performance vehicles. It is a Mid SAPS oil which meets the increasing demands of the latest & future generation gasoline & diesel engines and provides protection to the Diesel Particulate Filter.

## APPLICATIONS

OKINAWA SYNTHETIC ENGINE OIL C3 SAE 0W-30 SP, is recommended for all types of modern gasoline-powered vehicles, including high-performance turbocharged, supercharged, multi-valve fuel injected engines found in passenger cars, SUVs, light vans and light trucks.

- Recommended for SAE 0W-30, 5W-30 and 10W-30 applications.
- Recommended for extreme cold conditions to help deliver quick starts and fast lubrication.
- Not recommended for 2-Cycle or aviation engines, unless specifically approved by the manufacturer.

## PERFORMANCE FEATURES AND BENEFITS

- Low viscosity, advanced full synthetic formula
- LSPI protection and chain wear protection
- Outstanding thermal and oxidation stability
- Outstanding low temperature capabilities
- Active cleaning agents
- Precisely balanced additive component system
- Protects both diesel and gasoline particulate filters.

## RECOMMENDATIONS / SPECIFICATIONS

ACEA C3

API SP

BMW LONGLIFE-04

MB 229.51, MB 229.31, MB 229.52

PORSCHE C30

VW 504.00/507.00

## TYPICAL TECHNICAL PROPERTIES

Viscosity Grade, SAE J300	0W-30
Product code	2547PV
Density at 15°C, g/ml, ASTM D4052	0.841
Cold Cranking Viscosity(CCS), mPa s, ASTM D5293	5950@-35°C
Kinematic Viscosity at 40°C, mm <sup>2</sup> /s, ASTM D445	59.99
Kinematic Viscosity at 100°C, mm <sup>2</sup> /s, ASTM D445	10.75
Viscosity Index, ASTM D2270	172
Flash Point(COC), °C, ASTM D92	226
Pour Point, °C, ASTM D97	-42
Total Base Number, mg KOH/g, ASTM D2896	8.4

Note: These characteristics are typical of current production. While future production will conform to current specification, variations in these characteristics may occur.

PDS/AL/057/0\*, 10.02.22, Page 1/1  
\* supersedes all previous versions

*Health and Safety: Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contact office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.*